

SIGNMAX® PREMIUM DRY ERASE OVERLAMINATE

Technical Data Sheet

Product Description

- For indoor use with dry erase type markers. Polyester has a dry-erase coating for longer-term dry-erase capabilities. Laminate may be written on repeatedly; wipes clean with dry tissue or dry erase cleaning fluid. It readily laminates to any smooth sealed surface.

Construction

Value	Characteristic
Composition	Clear Polyester
Thickness of Vinyl	1 mil
Adhesive	Clear Permanent Acrylic
Liner	78 lb paper
Gloss Level	90 (avg) @ 60'

Typical Performance Values

- The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Physical Properties

Value	Characteristic
Durability	Indoors for up to 2 Years
Minimum Application Temperature	10°C (50°F)
Service Temperature Range	-40°C - 60°C (-40°F - 180°F)
Chemical Resistance	Resistant to ammonium hydroxide - 10%, detergent, distilled water, gasoline and hydrochloric acid - 10%.
Typical Adhesive Values	180° Peel Test Substrate 24hrs Stainless Steel 2.5 lb/in
Shelf Life	1 year from ship date when stored in proper conditions 20°C (70°F) and 50% relative humidity.