3M[™] DI-NOC[™] DW-1900HMT ABACUS WALNUT MATTE

Product Family: Dry Wood **Product Use: Architectural Finishes** Roll Width: 1220 mm (48 inches) Roll Length: 50,000 mm (50 metres) Thickness: 8 mils (200 microns) some designs vary slightly in thickness due to embossing Pattern Direction: Horizontal Weight: 0.035 per square foot Content: Vinyl Backing: Acrylic pressure sensitive adhesive, permanent Release Liner: Silicone-coated poly paper Cleaning: 70/30 IPA (70% Isopropyl alcohol/30% water) Flammability: CAN/ULC-S102.2 (all finishes) VOC Emisison Testing: CA specification 01350 tested per CDPH standard method V1.1 and V1.2 compliant as low-emitting Wear Resistance: 7,000 taber cycles Application Surface Type: Smooth, hard, non-porous (sealed) material **Application Location: Interior** Materials Reuse: Product can be used to refinish salvaged, refurbished, or reused materials and furniture Application Temperature: (12°C - 38°C) air and application surface Application Method: Dry application Warranty: 10 years



WRI



Product may vary in color, texture, finish and scale

Origin: Japan

Product Characteristics Product Performance Stain Resistance Resistance to Solvents, Cleaners and other Chemicals Cleaning and Maintenance Application and Removal Adhesion Compatibility with Application Surfaces