3M[™] DI-NOC[™] FW-1752H WEATHERVANE WALNUT

Product Family: Fine Wood Product Use: Architectural Finishes Roll Width: 1220 mm (48 inches) Roll Length: 50,000 mm (50 metres) Thickness: 8 mils (200 microns) some designs vary slightly in thickness due to embossing Pattern Direction: Horizontal Weight: 0.035 per square foot Content: Vinyl Backing: Acrylic pressure sensitive adhesive, permanent Release Liner: Silicone-coated poly paper Cleaning: 70/30 IPA (70% Isopropyl alcohol/30% water) Flammability: CAN/ULC-S102.2 (all finishes) VOC Emisison Testing: CA specification 01350 tested per CDPH standard method V1.1 and V1.2 compliant as low-emitting Wear Resistance: 7,000 taber cycles Application Surface Type: Smooth, hard, non-porous (sealed) material **Application Location: Interior** Materials Reuse: Product can be used to refinish salvaged, refurbished, or reused materials and furniture Application Temperature: (12°C - 38°C) air and application surface Application Method: Dry application Warranty: 10 years Origin: Japan

Product Characteristics Product Performance Stain Resistance Resistance to Solvents, Cleaners and other Chemicals Cleaning and Maintenance Application and Removal Adhesion Compatibility with Application Surfaces



WRI



Product may vary in color, texture, finish and scale