3M™ DI-NOC™ VM-1488 BLACK GOLD DIAGONAL



Product Family: Metallic

Product Use: Architectural Finishes
Roll Width: 1220 mm (48 inches)
Roll Length: 25,000 mm (25 metres)

Thickness: 8 mils (200 microns) some designs vary slightly in thick-

ness due to embossing

Weight: 0.035 per square foot

Content: Vinyl

Backing: Acrylic pressure sensitive adhesive, permanent

Release Liner: Silicone-coated poly paper

Cleaning: 70/30 IPA (70% Isopropyl alcohol/30% water)

Flammability: CAN/ULC-S102.2 (all finishes)

VOC Emisison Testing: CA specification 01350 tested per CDPH

standard method V1.1 and V1.2 compliant as low-emitting

Wear Resistance: 7,000 taber cycles

Application Surface Type: Smooth, hard, non-porous (sealed) material

VM Series: Do not use on compound curved surfaces. Film may bubble

on plastic substrates that outgas.

Application Location: Interior

Materials Reuse: Product can be used to refinish salvaged, refurbished,

or reused materials and furniture

Application Temperature: (12°C - 38°C) air and application surface

Application Method: Dry application

Warranty: 10 years

Origin: Japan

Product Characteristics
Product Performance
Stain Resistance

Resistance to Solvents, Cleaners and other Chemicals

Cleaning and Maintenance Application and Removal

Adhesion Compatibility with Application Surfaces





Product may vary in color, texture, finish and scale