## 3M™ DI-NOC™ LE-703EX PEPPERCORN LEATHER EXTERIOR



**Product Family: Leather** 

Product Use: Architectural Finishes
Roll Width: 1220 mm (48 inches)
Roll Length: 50,000 mm (50 metres)

Thickness: 8 mils (200 microns) some designs vary slightly in thick-

ness due to embossing

Weight: 0.035 per square foot

Content: Vinyl

Backing: Acrylic pressure sensitive adhesive, permanent

Release Liner: Silicone-coated poly paper

Cleaning: 70/30 IPA (70% Isopropyl alcohol/30% water)

Flammability: CAN/ULC-S102.2 (all finishes)

VOC Emisison Testing: CA specification 01350 tested per CDPH stan-

dard method V1.1 and V1.2 compliant as low-emitting

Wear Resistance: 3,000 taber cycles

Application Surface Type: Smooth, hard, non-porous (sealed) material

Application Location: Exterior

Materials Reuse: Product can be used to refinish building façades, window frames, doors, columns, walls and other exterior surfaces.

Application Temperature: (12°C - 38°C) air and application surface

Application Method: Dry application

Warranty: 10 years

Origin: Japan





Product may vary in color, texture, finish and scale

Product Characteristics
Product Performance
Stain Resistance
Resistance to Solvents, Cleaners and other Chemicals
Cleaning and Maintenance
Application and Removal
Adhesion Compatibility with Application Surfaces